Brute Force 650 4x4i specifications

Engine

Engine type
Liquid-cooled, 4-stroke 90° V-twin
Displacement
633 cm³
Bore x stroke
80 x 63 mm
Compression ratio
9.9:1
Valve system
SOHC, 8 valves
Fuel system
Carburettor: 2x Keihin CVKR-34
Starting System
Electric with recoil back up

Brakes & Suspension

Brakes, front
200 mm discs with twin piston calipers
Brakes, rear
Sealed multi-plate system
Suspension, front
Double Wishbone
Suspension, rear
Double Wishbone

Performance & Transmission

Maximum power
34.7 kW {47 PS} / 7,500 rpm

Maximum torque
51.4 N • m {5.2 kgf • m} / 5,500 rpm

Transmission
2-speed automatic with reverse

Final drive
Shaft 2WD/4WD

Frame & Dimensions

Frame type
Double tubular
Trail

2° / 12 mm

Wheel travel front

171 mm

Wheel travel rear

200 mm

Tyre, front

AT 25 x 8-12 (tubeless)

Tyre, rear

AT 25 x 10-12

LxWxH

2,195 x 1,165 x 1,235 mm

Wheelbase

1,285 mm

Ground clearance

245 mm

Fuel capacity

20.5 litres

Curb mass

298 kg